



Equipment STANDARD

- Stainless-steel structure
- Comfort upholstery
- Low-noise chair movement with soft start and stop
- 5 chair positions can be stored
- Automatically folding leg rest for easy entry and exit of the patient
- Doctor's device with touchscreen on a freely movable base
- Cuspidor as a stainless-steel column with
 - Bottle Care System or
 - Water treatment with water separation unit in accordance with EN 1717 and EN 7494-2
- Swivelling assistant's device with saliva ejector and spray mist suction
- Wireless foot controller

D2-EC

Doctor's device on a freely movable base for flexible positioning



Equipment OPTIONAL

- Left and/or right arm rest
- Height-adjustable tray
- Operating Lamp LED.light EVA
- 3-function syringe in the assistant's device
- 2nd saliva ejector in the assistant's device
- Integrated dry or wet suction system



CONFIGURATION

at the D2-EC doctor's device

Page	Available	Applied part
38 / 39	•	Touchscreen
34	•	Standard turbine connection
35	•	Advanced-Air turbine
34	•	EM-12 L micromotor
37	•	Piezo scaler
-	•	3-function syringe*
36	•	Implantmed Plus

* Mounted optionally on left or right side



Surgical unit
Info on page 36

In cooperation with
W&H

implantmed plus



Wireless foot controller